

Application Serial No. 10/763,500

Page 11 of 30

Date May 16, 2005

Reply to Office Action dated February 15, 2005

Listing of the Claims:

1. (Currently amended) A position control system for a fluid operated cylinder having at least one fluid chamber defined by a piston located within a housing for movement between first and second end limits of travel, the system comprising:

at least two electrically actuated proportional flow valves connected to each port of the fluid operated cylinder to be controlled for selectively and proportionally controlling fluid flow into and out of the at least one fluid chamber of the fluid operated cylinder to be controlled;

at least one pressure sensor for measuring fluid pressure with respect to each chamber of the fluid operated cylinder to be controlled;

at least one discrete position sensor including a first position sensor located adjacent a midpoint of the fluid operated cylinder to be controlled for sensing a discrete centered position of the piston within the cylinder; and

a controller having a control program operably connected to the at least two valves, the at least one pressure sensor, and the at least one position sensor for controlling actuation of the at least two valves in response to pressure measured by the at least one pressure sensor and location measured by the at least one position sensor.

2. (Currently amended) The system of claim 1, wherein the at least one discrete position sensor further comprises:

~~a first position sensor located adjacent a midpoint of the fluid operated cylinder; and~~

a second position sensor located adjacent one end of travel of the piston in the housing for providing soft stop deceleration of the piston prior to contact with an end wall of the housing defining the at least one chamber.

3. (Original) The system of claim 1 further comprising:

Application Serial No. 10/763,500

Date May 16, 2005

Reply to Office Action dated February 15, 2005

Page 12 of 30

the at least two electrically actuated proportional flow valves including a first valve associated with the first expandable fluid chamber for selectively and proportionally controlling fluid flow into the first expandable fluid chamber and a second valve associated with the first expandable fluid chamber for selectively and proportionally controlling fluid flow out of the first expandable fluid chamber.

4. (Original) The system of claim 1 further comprising:

the at least one expandable fluid chamber including a first expandable fluid chamber adjacent one end of travel of the piston in the housing and a second expandable fluid chamber adjacent another end of travel of the piston in the housing.

5. (Original) The system of claim 4 further comprising:

the at least one pressure sensor includes a first pressure sensor associated with the first expandable fluid chamber and a second pressure sensor associated with the second expandable fluid chamber.

6. (Currently amended) The system of claim 4 further comprising:

the at least one discrete position sensor including a ~~first position sensor located adjacent a midpoint of the fluid operated cylinder,~~ a second position sensor located adjacent one end of travel of the piston in the housing for providing soft stop deceleration of the piston prior to contact with an end wall of the housing defining one chamber, and a third position sensor located adjacent an opposite end of travel of the piston in the housing for providing soft stop deceleration of the piston prior to contact with an end wall of the housing defining another chamber.

7. (Currently amended) The system of claim 1 ~~further comprising:~~

wherein the control program for initializing is operable to initialize a home position when the piston is sensed by the at least one discrete first position sensor located adjacent the midway position with respect to the housing.

Application Serial No. 10/763,500

Page 13 of 30

Date May 16, 2005

Reply to Office Action dated February 15, 2005

8. (Currently amended) The system of claim 1 further comprising:
the controller having the control program for calculating a required pressure in the at least one expandable fluid chamber for moving the piston a desired distance within the housing from the discrete centered position located midway with respect to the housing, and for controlling the at least two electrically actuated proportional flow valves to obtain the calculated pressure within the at least one expandable fluid chamber corresponding to the desired distance of movement for the piston within the housing.

9. (Original) The system of claim 1 further comprising:
means for biasing the piston toward the discrete centered position with respect to the housing.

10. (Currently amended) A process for operating a position control system for a fluid operated cylinder having at least one fluid chamber defined by a piston located within a housing for movement between first and second end limits of travel, the system process comprising the steps of:

selectively and proportionally controlling fluid flow into and out of the at least one fluid chamber of the fluid operated cylinder to be controlled with at least two electrically actuated proportional flow valves connected to each port of the fluid operated cylinder to be controlled;

measuring fluid pressure with respect to each chamber of the fluid operated cylinder to be controlled with at least one pressure sensor;

sensing a ~~discrete centered~~ position of the piston within the cylinder with at least one discrete position sensor, the at least one discrete position sensor including a first position sensor located adjacent a midpoint of the fluid operated cylinder to be controlled; and

controlling actuation of the at least two valves in response to pressure

Application Serial No. 10/763,500

Date May 16, 2005

Page 14 of 30

Reply to Office Action dated February 15, 2005

measured by the at least one pressure sensor and location measured by the at least one position sensor with a controller having a control program operably connected to the at least two valves, the at least one pressure sensor, and the at least one position sensor.

11. (Currently amended) The ~~system~~ process of claim 10, wherein ~~the position sensing step with the at least one discrete position sensor further comprises~~ comprising the steps of:

~~locating a first position sensor adjacent a midpoint of the fluid operated cylinder; and~~

~~locating a second position sensor adjacent one end of travel of the piston in the housing;~~

sensing a discrete position adjacent one end of travel of the piston with respect to the housing with ~~the~~ a second position sensor, the second position sensor adjacent one end of travel of the piston in the housing; and

~~decelerating the piston to a soft stop prior to contact with an end wall of the housing defining the at least one chamber with the control program controller in response to the second position sensor.~~

12. (Currently amended) The ~~system~~ process of claim 10, wherein the controlling fluid flow step with at least two electrically actuated proportional flow valves further comprises the steps of:

providing a first valve associated with the first expandable fluid chamber for selectively and proportionally controlling fluid flow into the first expandable fluid chamber; and

providing a second valve associated with the first expandable fluid chamber for selectively and proportionally controlling fluid flow out of the first expandable fluid chamber.

Application Serial No. 10/763,500

Page 15 of 30

Date May 16, 2005

Reply to Office Action dated February 15, 2005

13. (Currently amended) The ~~system process~~ of claim 10 wherein the at least one expandable fluid chamber further comprises the steps of:
providing a first expandable fluid chamber adjacent one end of travel of the piston in the housing; and
providing a second expandable fluid chamber adjacent another end of travel of the piston in the housing.

14. (Currently amended) The ~~system process~~ of claim 13, wherein the pressure sensing step with at least one pressure sensor further comprises the steps of:
providing a first pressure sensor associated with the first expandable fluid chamber; and
providing a second pressure sensor associated with the second expandable fluid chamber.

15. (Currently amended) The ~~system process~~ of claim 13, wherein ~~the position sensing step with at least one discrete position sensor further comprises comprising the steps of:~~
~~providing a first position sensor located adjacent a midpoint of the fluid operated cylinder;~~
providing a second position sensor located adjacent one end of travel of the piston in the housing for providing soft stop deceleration of the piston prior to contact with an end wall of the housing defining one chamber; and
providing a third position sensor located adjacent an opposite end of travel of the piston in the housing for providing soft stop deceleration of the piston prior to contact with an end wall of the housing defining another chamber.

16. (Currently amended) The ~~system process~~ of claim 10, wherein the controlling step with a control program further comprises the step of:

Application Serial No. 10/763,500

Date May 16, 2005

Reply to Office Action dated February 15, 2005

Page 16 of 30

initializing a home position when the piston is sensed by the at least one discrete position sensor to be located at the discrete centered position with respect to the housing.

17. (Currently amended) The ~~system~~ process of claim 10, wherein the controlling step with a control program further comprises the steps of:

calculating a required pressure in the at least one expandable fluid chamber for moving the piston a desired distance within the housing from the discrete centered position located midway with respect to the housing; and
controlling the at least two electrically actuated proportional flow valves to obtain the calculated pressure within the at least one expandable fluid chamber corresponding to the desired distance of movement for the piston within the housing.

18. (Currently amended) The ~~system~~ process of claim 10 further comprising the step of:

biasing the piston toward the discrete centered position with respect to the housing.

19. (Currently amended) A position control system for a fluid operated cylinder having two fluid chambers defined by a piston located within a housing for movement between first and second end limits of travel, the system comprising:

four electrically actuated proportional flow valves, two valves connected to each port of the fluid operated cylinder to be controlled for selectively and proportionally controlling fluid flow into and out of the two fluid chambers of the fluid operated cylinder to be controlled;

two pressure sensors, one pressure sensor for measuring fluid pressure with respect to each chamber of the fluid operated cylinder to be controlled;

Application Serial No. 10/763,500

Page 17 of 30

Date May 16, 2005

Reply to Office Action dated February 15, 2005

at least one discrete position sensor including a first position sensor located adjacent a midpoint of the fluid operated cylinder to be controlled for sensing a discrete centered position of the piston within the cylinder; and

a controller having a control program operably connected to the four valves, the two pressure sensors, and the at least one position sensor for controlling actuation of the four valves in response to pressure measured by the two pressure sensors and location measured by the at least one position sensor.

20. (Currently amended) The system of claim 19 further comprising:

the at least one discrete position sensor including ~~a first position sensor located adjacent a midpoint of the fluid operated cylinder,~~ a second position sensor located adjacent one end of travel of the piston in the housing for providing soft stop deceleration of the piston prior to contact with an end wall of the housing defining the first chamber, and a third position sensor located adjacent an opposite end of travel of the piston in the housing for providing soft stop deceleration of the piston prior to contact with an end wall of the housing defining the second chamber.

21. (Currently amended) The system of claim 19 ~~further comprising:~~ wherein the control program ~~for initializing is operable to initialize~~ a home position when the piston is sensed by the at least one discrete position sensor located adjacent the midway position with respect to the housing.

22. (Currently amended) The system of claim 19 further comprising:

the controller having the control program for calculating a required pressure in each of the first and second expandable fluid chambers for moving the piston a desired distance within the housing from the discrete centered position located midway with respect to the housing, and for controlling the four electrically

Application Serial No. 10/763,500

Date May 16, 2005

Page 18 of 30

Reply to Office Action dated February 15, 2005

actuated proportional flow valves to obtain the calculated pressure within each of the first and second expandable fluid chambers corresponding to the desired distance of movement for the piston within the housing.

23. (Currently amended) A position control system for a fluid operated cylinder having at least one fluid chamber defined by a piston located within a housing for movement between first and second end limits of travel, the system comprising:

at least two electrically actuated proportional flow valves connected to each port of the fluid operated cylinder to be controlled for selectively and proportionally controlling fluid flow into and out of the at least one fluid chamber of the fluid operated cylinder to be controlled;

at least one discrete position sensor associated with the fluid operated cylinder to be controlled for sensing a discrete position of the piston within the cylinder;

a supply of pressurized fluid in communication with the at least two electrically actuated proportional flow valves at a predetermined pressure; and

a controller having a control program operably connected to the at least two valves and the least one position sensor for controlling actuation respective positions of the at least two valves in response to position measured by the at least one position sensor.

24. (Previously presented) The system of claim 23, wherein the at least one discrete position sensor further comprises:

a first position sensor located adjacent a midpoint of the fluid operated cylinder; and

a second position sensor located adjacent one end of travel of the piston in the housing for providing soft stop deceleration of the piston prior to contact with an end wall of the housing defining the at least one chamber.

Application Serial No. 10/763,500

Page 19 of 30

Date May 16, 2005

Reply to Office Action dated February 15, 2005

25. (Previously presented) The system of claim 23 further comprising:

the at least two electrically actuated proportional flow valves including a first valve associated with the first expandable fluid chamber for selectively and proportionally controlling fluid flow into the first expandable fluid chamber and a second valve associated with the first expandable fluid chamber for selectively and proportionally controlling fluid flow out of the first expandable fluid chamber.

26. (Previously presented) The system of claim 23 further comprising:

the at least one expandable fluid chamber including a first expandable fluid chamber adjacent one end of travel of the piston in the housing and a second expandable fluid chamber adjacent another end of travel of the piston in the housing.

27. (Previously presented) The system of claim 26 further comprising:

the at least one discrete position sensor including a first position sensor located adjacent a midpoint of the fluid operated cylinder, a second position sensor located adjacent one end of travel of the piston in the housing for providing soft stop deceleration of the piston prior to contact with an end wall of the housing defining one chamber, and a third position sensor located adjacent an opposite end of travel of the piston in the housing for providing soft stop deceleration of the piston prior to contact with an end wall of the housing defining another chamber.

28. (Currently amended) The system of claim 23 ~~further comprising:~~ wherein the control program for initializing is operable to initialize a home position when the piston is sensed by the at least one discrete position sensor located adjacent the midway position with respect to the housing.

Application Serial No. 10/763,500

Page 20 of 30

Date May 16, 2005

Reply to Office Action dated February 15, 2005

29. (Currently amended) The system of claim 23 further comprising:

the controller having the control program for calculating a required pressure in the at least one expandable fluid chamber for moving the piston a desired distance within the housing from the discrete centered position located midway with respect to the housing, and for controlling the at least two electrically actuated proportional flow valves to obtain the calculated pressure within the at least one expandable fluid chamber corresponding to the desired distance of movement for the piston within the housing.

30. (Previously presented) The system of claim 23 further comprising:

means for biasing the piston toward the discrete center position with respect to the housing.